

Chlorine Dioxide Solution

CLO2 Chemical

(3000 ppm, 99.7% Pure)

Applications:

- Municipal Water
- Wastewater
- Oil / Gas
- H2S Scavenger
- Wells
- Produce Water
- Beverage Industry
- Agriculture
- Cooling Towers
- Food Industry
- Legionella
- Taste / Odor Control

TCEQ APPROVED FOR POTABLE
WATER SYSTEMS AS PRIMARY
DISINFECTANT

Used for Trials or
Low Demand Applications



Actual containers may vary

Available in a variety of Containers
5 – 265 Gallons

Features:

- 99.7% pure, pH neutral solution, free of reaction bi-products
- Easy to use and handle for trials of small volume applications
- Dry-Mate connections (limited CLO2 exposure)
- Generated with NSF certified generator and pre-cursor
- Capable of being fed in multiple configurations
- Relatively short lead-times, reduced inventory requirements

Container Size	Gallons Delivered	CLO2 Lbs in Container
265 Gallon	260 Gallons	6.8 Lbs
55 Gallon	53 Gallons	1.4 Lbs.
30 Gallon	27 Gallons	0.7 Lbs
15 Gallon	12.5 Gallons	0.3 Lbs.
5 Gallon	4 Gallons	0.1 Lbs.

EPA Registered, TCEQ, FDA, NSF Certified