

# Series 230 Control Valve

ol Valve

### Reliable Automatic Chemical Feed Control...

- Superb Accuracy and Repeatability
- Compact Design / Simple Operation
- Versatile Gas or Liquid Feed Control
- Designed for Minimal Wear & Long Life

The Hydro Instruments Series 230 Control Valve offers a simple and accurate solution for automatic chemical feed. The valve uses a linear-drive motor to ensure the least possible wear and longest life of the valve components. It is designed to be compact, reliable and easy to use.

## **Highlights**

Linear Operation Eliminates Gears and All Rotating Motion Broad Range of Capacities and Chemicals 2x20 Character LCD Display Simple 4 Push Button Interface Password Protected Settings

By replacing rotating assemblies with a simple linear design and incorporating a lengthened v-notch stem, Hydro Instruments CV-230 Control Valve produces precise and repeatable feed rate control with minimal wear.

State-of-the-art microprocessor technology, high quality materials of construction and precision machining of a minimal number of moving parts combine make the Series 230 Control Valve both accurate and dependable over long periods of continuous operation.





600 Emlen Way, Telford, PA 18969 • Telephone: (215) 799-0980 • Fax: (215) 799-0984
 Toll Free in the U.S.: 1 (888) 38-HYDRO • www.hydroinstruments.com • sales@hydroinstruments.com

# Series 230 Control Valve

#### **CV-230 Ordering Information**

CV-230		<b>-</b>
<ul> <li>MAX CAPACITY</li> <li>1. 500 ppd (10 kg/hr)</li> <li>2. 2000 ppd (40 kg/hr)</li> <li>3. 3000 ppd (60 kg/hr)</li> </ul>		
<ul> <li>GAS OR LIQUID</li> <li>A. Ammonia (NH<sub>3</sub>)</li> <li>B. Sodium Bisulfite (NaHSO<sub>3</sub>)</li> <li>C. Chlorine (Cl<sub>2</sub>)</li> <li>S. Sulfur Dioxide (SO<sub>2</sub>)</li> <li>H. Sodium Hypochlorite (NaOCI)</li> <li>Other: Consult Factory</li> </ul>		
<b>PANGE</b> 1. 10 ppd (200 gr/hr)         2. 25 ppd (500 gr/hr)         3. 50 ppd (1 kg/hr)         4. 100 ppd (2 kg/hr)         5. 250 ppd (5 kg/hr)         6. 500 ppd (10 kg/hr)         7. 1000 ppd (20 kg/hr)         8. 2000 ppd (40 kg/hr)         9. 3000 ppd (60 kg/hr)		
Note: For liquid use please specify the desired max ca	apacity.	

#### **POWER REQUIREMENT**

- **1.** 120V 60Hz
- 2. 240V 50Hz





600 Emlen Way, Telford, PA 18969 • Telephone: (215) 799-0980 • Fax: (215) 799-0984 Toll Free in the U.S.: 1 (888) 38-HYDRO • www.hydroinstruments.com • sales@hydroinstruments.com